

MANUFACTURE DATE: 08/05/2019

Inspection Certificate

Abnahmeprufzeugnis DIN EN 10204 3.1 Certificat De reception Certificado di collaudo Keuringsrapport

AEROSOL BATCH No: 1904225 B.B.E.: MAY 2024

We hereby certify that when tested at the time of manufacture, the above material:

- 1. Meets the requirements of and has been tested for sulfur and halogens according to:
 - a) ASME Boiler and pressure Vessel Code, 2004, 2007, 2010, 2013, 2015 & 2017 Edition, Section V, including 2005, 2006, 2008,2009&2011a Addendum, Nondestructive Examination, Article 6 Paragraph T-641 & Article 24 as applicable. Anion analysis by ASTM D129 decomposition followed by Ion Chromatography method Annex A4.
 - b) ASTM E-165/E-165M-18, Paragraph 7.1.

SUBJECT: Spotcheck SKL-SP2 Red Penetrant

- c) MIL-STD-271F (SH), 27 June 86, Paragraph 5.3 and 5.3.1 including notice 1 Paragraph 5.6.1 (21 June 1993).
- d) MIL-STD-2132D, 11 February 2003, Paragraph 7.1, 7.1.2, 7.1.3 and Appendix C, Paragraph 40.

Test results obtained were as follows	<u>s:</u>	
Sulfur:0.0007 wt % of residue.		Chlorine + Fluorine:0.0017 wt % of residue.
Cleaner residue (See note 3)	g/100g	g/100ml

 Meets the requirements of EN ISO 3452-1, EN ISO 3452-2 (Sensitivity level 2), AMS 2644G and ASTM E 1417/E 1417M-16 Paragraph 5.1& 6.5.1.

When tested according to paragraph 4.3.2 of AMS 2644G the following results were obtained:

4.2.2.1	Penetrant Tests Flashpoint (PMCC) (3.3.3) Viscosity (3.3.4) Fluorescent Brightness (3.3.8.3.2) Water tolerance Method A, B, C & D (3.3.8.5) Penetrant Removability (3.3.8.6) Water Content (3.3.8.7)		109°C 3.62 mm²/s (cSt) @ 38°C N/A Not water soluble Conforms <0.23%
4.2.2.2	Emulsifier Tests Flashpoint (PMCC) (3.3.3) Viscosity (3.3.4) Water Content Method D only (3.3.9.6)	:	N/A N/A N/A
4.2.2.3	Developer Tests Developer Fluorescence (3.3.10.2) Developer Removability (3.3.10.4) Redispersibility (3.3.10.5)	-	N/A N/A N/A
3.3.11.5	Solvent Remover Tests Penetrant Removal (4.4.11.2)	:	N/A

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Certification is issued under the auspices of the Quality Assurance Manager.

(Authorised Employee)

For and on behalf of MAGNAFLUX (A DIVISION OF ITW LTD)

Notes:

- 1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container. Bulk materials have a minimum shelf life of 5 years from date of manufacture. Aerosols have a minimum shelf life of 3 years from date of manufacture.
- 2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
- MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According
 to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
- 4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

FORMAT:MX 101.137 SK MC-05 Rev 15

Magnaflux (A Division of ITW Ltd), Faraday Road, South Dorcan Industrial Estate, Swindon, Wiltshire, SN3 5HE, UK





SUBJECT: SpotcheckSKL-SP2 Red Penetrant

BATCH No:1904225

B.B.E.: MAY 2024

MANUFACTURE DATE:08/05/2019

Specification: EN ISO 3452-2

When tested at the time of manufacture the following results were obtained:

Einzeleigenschaft / Characteristic	Ermittlungen nach EN ISO 3452-2 Abschnitt	Anforderungen / Quality requirement	Ergebnis / Batch testing
Appearance	6.1	Equal to Std	Pass
Sensitivity	6.2	Level 2	Pass
Density	6.3	0.806.0.890 g/cm3 @ 20°C	0.848 g/cm ³
Viscosity	6.4	3.24 . 3.96 mm²/s @ 38°C	3.62 mm ² /s
Flashpoint	6.5	93°C Min for Bulk	Bulk 109°C Aerosol -40°C
Washability	6.6	Equal to Std (Water Wash Pen Only)	N/A
Corrosive Properties	6.11	No Corrosion on Magnesium Alloy	Pass
Sulphur Content	6.12	< 200 ppm	7 ppm
Halogen Content	6.12	< 200 ppm	17 ppm
Water Content	6.20	< 5% (Water Wash Pen Only)	N/A

VorstehendeAngabensind die ErgebnisseunsererQualitätsprüfung. Sie entbinden den Käufernicht von einerEingangsprüfung und habennicht die Bedeutung, die Eignung des ProduktesfüreinenkonkretenEinsatzzweckzuzusichern.

The above information is derived from our quality checks. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of the product for any particular purpose.

Certification is issued under the auspices of the Quality Assurance Manager.

Authorised Employee)

Dastat

For and on behalf of MAGNAFLUX (A DIVISION OF ITW LTD)

Magnaflux (A Division of ITW Ltd), Faraday Road, South Dorcan Industrial Estate, Swindon, Wiltshire, SN3 5HE, UK