

**MANUFACTURE DATE:**15/08/2019Abnahmeprufzeugnis DIN EN 10204 3.1  
Certificat De reception  
Certificado di collaudo  
Keuringsrapport**SUBJECT:** Zyglo ZP-5B Water Suspendible Developer**BATCH No:**1908511  
**B.B.E.:** AUG 2024

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:
  - a) ASME Boiler and Pressure Vessel Code, 2019 Edition, Section V, Non-destructive Examination.
  - b) Anion analysis by ASTM D129 decomposition followed by Ion Chromatography method Annex A4.
  - c) ASTM E-165/E-165M-18, Paragraph 7.1.
  - d) MIL-STD-2132D, 11 February 2003, Paragraph 7.1, 7.1.2, 7.1.3 and Appendix C, Paragraph 40.

**Test results obtained were as follows:****Sulfur:**0.0031 wt % of residue.**Chlorine + Fluorine:**0.0017 wt % of residue.

Cleaner residue (See note 3)      g/100g      g/100ml

2. Meets the requirements of AMS 2644G and ASTM E 1417/E 1417M-16 Paragraph 5.1 & 6.5.1.  
When tested according to paragraph 4.3.2 of AMS 2644G the following results were obtained:

**4.2.2.1 Penetrant Tests**

Flashpoint (PMCC) (3.3.3)	:	N/A
Viscosity (3.3.4)	:	N/A
Fluorescent Brightness (3.3.8.3.2)	:	N/A
Water tolerance Method A, B, C & D (3.3.8.5)	:	N/A
Penetrant Removability (3.3.8.6)	:	N/A
Water Content (3.3.8.7)	:	N/A

**4.2.2.2 Emulsifier Tests**

Flashpoint (PMCC) (3.3.3)	:	N/A
Viscosity (3.3.4)	:	N/A
Water Content Method D only (3.3.9.6)	:	N/A

**4.2.2.3 Developer Tests**

Developer Fluorescence (3.3.10.2)	:	Conforms
Developer Removability (3.3.10.4)	:	Conforms
Redispersibility (3.3.10.5)	:	Conforms

**3.3.11.4 Solvent Remover Tests**

Penetrant Removal (4.4.11.2)	:	N/A
------------------------------	---	-----

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Certification is issued under the auspices of the Quality Assurance Manager.

  
(Authorised Employee)

For and on behalf of MAGNAFLUX (A DIVISION OF ITW LTD)

**Notes:**

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container. Bulk materials have a minimum shelf life of 5 years from date of manufacture. Aerosols have a minimum shelf life of 3 years from date of manufacture.
2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.