

**Inspection Certificate**

Abnahmeprüfungszeugnis DIN EN 10204.3.1  
 Certificat De reception  
 Certificado di collaudo  
 Keuringsrapport



|                            |                       |                     |                           |
|----------------------------|-----------------------|---------------------|---------------------------|
| <b>Batch Number</b>        | <b>231007</b>         | <b>Product Name</b> | Bycotest D30 plus Aerosol |
| <b>Date of Manufacture</b> | 05/10/2023 06/10/2023 | <b>B.B.E.</b>       | 10/2026                   |

**Specification: Test Results**

Sulphur and Halogen levels according to ASME B&PV Code Section V.

We are accredited to EN ISO 9001: 2015

| Test                  | Section                  | Limit    | Result  |
|-----------------------|--------------------------|----------|---------|
| Appearance            | 6.1 in EN ISO 3452-2     | Equal to | Passed  |
| Re-Dispersion         | 6.16 in EN ISO 3452-2    | Equal to | Passed  |
| Developer Performance | 6.15 in EN ISO 3452-2    | Equal to | Passed  |
| Halogen Content       | ASME BPVC Code Section V | <1000ppm | 167 ppm |
| Sulphur Content       | ASME BPVC Code Section V | <1000ppm | 18 ppm  |

--- EOR ---

**Prepared by**

**Approved by**

**Notes:**

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.