

Inspection Certificate

Abnahmeprüfungszeugnis DIN EN 10204.3.1
Certificat De reception
Certificado di collaudo
Keuringsrapport



Batch Number	2402004	Product Name	Spotcheck SKL-WP2 Water Washable Red Penetrant
Date of Manufacture	01/02/2024	B.B.E.	02/2029

Specification: Specification

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:

- a) ASME Boiler and Pressure Vessel Code, 2023 Edition, Section V, Non-destructive Examination.
- b) ASTM E-165/E-165M-18, Paragraph 7.1.
- c) MIL-STD-2132E, March 29, 2016, Paragraph 6.1.3.

2. Meets the requirements of EN ISO 3452-1, EN ISO 3452-2 (Sensitivity level 2), AMS 2644H and ASTM E 1417/E 1417M-21 Paragraph 5.1& 6.5.1.

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Test	Section	Limit	Result
Specification			Passed

Specification: Ion Testing Results

Test results obtained were as follows:

Test	Section	Limit	Result
Sulphur Content			21 ppm
Halogen Content			69 ppm

Specification: AMS 2644H Penetrant Test Results

Type 2 Penetrant

When sampled and tested according to paragraph 4.3.2 section 4.2.2.1 of AMS 2644H the following results were obtained:

Test	Section	Limit	Result
Viscosity	3.3.4		8.14 mm ² /s
Water Tolerance (SMT 2)	3.3.8.5		Passed
Penetrant Removal	3.3.8.6		Passed
Water Content (SMT 18)	3.3.8.7		0.09 %
Flashpoint (SMT 14)	3.3.3	>93oC	104 °C

Specification: EN ISO 3452-2

When tested at the time of manufacture the following results were obtained. The information is derived from our quality checks. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of the product for any particular purpose.

Test	Section	Limit	Result
Appearance	6.1 in EN ISO 3452-2	Equal to standard	Passed
Sensitivity for ISO 3452-2 (SMT 58)	6.2 in EN ISO 3452-2	Level 2	Passed
Density (SMT 50)	6.3 in EN ISO 3452-2	0.875 – 0.900 g/cm ³ @ 20°C	0.888 g/cm ³
Viscosity	6.4 in EN ISO 3452-2	7.20 – 8.20 mm ² /s @ 38°C	8.14 mm ² /s
Washability (SMT 47)	6.5 in EN ISO 3452-2	Equal to Std (Water Wash Pen Only)	Passed
Corrosive Properties	6.11 in EN ISO 3452-2	No Corrosion on Magnesium Alloy	Passed
Sulphur Content	6.12 in EN ISO 3452-2	< 200 ppm	21 ppm

Inspection Certificate

Abnahmeprüfungszeugnis DIN EN 10204.3.1
Certificat De reception
Certificado di collaudo
Keuringsrapport



Halogen Content	6.12 in EN ISO 3452-2	< 200 ppm	69 ppm
Water Content (SMT 18)	6.20 in EN ISO 3452-2	< 5% (Water Wash Pen Only)	0.09 %
Flashpoint (SMT 14)	6.5 in EN ISO 3452-2	93°C Min for Bulk	104 °C

--- EOR ---

Prepared by

Approved by

Notes:

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.