

Inspection Certificate

Abnahmeprüfungszeugnis DIN EN 10204.3.1
 Certificat De reception
 Certificado di collaudo
 Keuringsrapport



| | | | |
|----------------------------|----------------|---------------------|---|
| Batch Number | 2402029 | Product Name | Zygly ZP-5B Water Suspendible Developer |
| Date of Manufacture | 07/02/2024 | B.B.E. | 02/2029 |

Specification: Specification**Specification**

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:

a) ASME Boiler and Pressure Vessel Code, 2023 Edition, Section V, Non-destructive Examination.

b) ASTM E-165/E-165M-18, Paragraph 7.1.

c) MIL-STD-2132E, March 29, 2016, Paragraph 6.1.3.

2. Meets the requirements of AMS 2644H and ASTM E 1417/E 1417M-21 Paragraph 5.1 & 6.5.1.

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Specification: Ion Testing Results

Test results obtained were as follows:

| Test | Section | Limit | Result |
|-----------------|---------|-------|---------|
| Sulphur Content | | | 43 ppm |
| Halogen Content | | | 485 ppm |

Specification: AMS 2644H Developer Results

When sampled & tested according to paragraph 4.3.2 section 4.2.2.3 of AMS 2644H the following results were obtained:

| Test | Section | Limit | Result |
|---------------------------------------|----------|-------|--------|
| Developer Fluorescence | 3.3.10.2 | | Passed |
| Developer Removability | 3.3.10.4 | | Passed |
| Redispersibility (Forms c,d & e only) | 3.3.10.5 | | Passed |

--- EOR ---

Prepared by

Approved by

Notes:

- Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
- Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
- MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
- The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

Magnaflux (A Division of ITW Ltd),
 Faraday Road, South Dorcan Industrial Estate,
 Swindon, Wiltshire, SN3 5HE, UK
 Tel: +44 (0)1793 524566
 Fax: +44 (0)1793 490459
 Email: sales.eu@magnaflux.com
 www.magnaflux.eu