

**Inspection Certificate**

Abnahmeprüfungszeugnis DIN EN 10204.3.1  
 Certificat De reception  
 Certificado di collaudo  
 Keuringsrapport



|                            |                       |                     |                                       |
|----------------------------|-----------------------|---------------------|---------------------------------------|
| <b>Batch Number</b>        | <b>241101</b>         | <b>Product Name</b> | Spotcheck SKD-S2<br>Developer Aerosol |
| <b>Date of Manufacture</b> | 19/11/2024 26/11/2024 | <b>B.B.E.</b>       | 11/2027                               |

**Specification: Specification**

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:

- a) ASME Boiler and Pressure Vessel Code, 2023 Edition, Section V, Non-destructive Examination.
- b) ASTM E-165/E-165M-18, Paragraph 7.1.
- c) MIL-STD-2132E, March 29, 2016, Paragraph 6.1.3.

2. Meets the requirements of EN ISO 3452-1, EN ISO 3452-2, SAFRAN Pr 5000 / In 5000D, AMS 2644H and ASTM E 1417/E 1417M-21 Paragraph 5.1 & 6.5.1.

3. Conforms to the chemical specifications of the PMUC reference 08-0226.

4. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

| Test          | Section | Limit | Result |
|---------------|---------|-------|--------|
| Specification |         |       | Passed |

**Specification: Ion Testing Results**

Test results obtained were as follows:

| Test            | Section | Limit    | Result |
|-----------------|---------|----------|--------|
| Sulphur Content |         | Conforms | 43ppm  |
| Halogen Content |         | Conforms | 184ppm |

**Specification: EN ISO 3452-2**

When tested at the time of manufacture the following results were obtained. The information is derived from our quality checks. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of the product for any particular purpose.

| Test                                | Section | Limit                           | Result      |
|-------------------------------------|---------|---------------------------------|-------------|
| Appearance                          | 6.1     | Equal to standard               | Passed      |
| Sensitivity for ISO 3452-2 (SMT 58) | 6.2     | Equal to standard               | Passed      |
| Corrosive Properties                | 6.11    | No Corrosion on Magnesium Alloy | Passed      |
| Solid Content (SMT 28)              | 6.13    | 9.0 - 15.0 %                    | 14.41 %     |
| Developer Performance               | 6.15    | Equal to standard               | Passed      |
| Re-Dispersion                       | 6.16    | Readily Dispersed               | Passed      |
| Density of Carrier Fluid            | 6.17    | 0.746 - 0.825 g/cm3             | 0.784 g/cm3 |

**Flashpoint (SMT 14)**

Aerosol -40°C

**Specification: AMS 2644H Developer Results**

When sampled according to paragraph 4.3.2 section 4.2.2.3 of AMS 2644H the following results were obtained:

| Test                                  | Section  | Limit    | Result |
|---------------------------------------|----------|----------|--------|
| Developer Fluorescence                | 3.3.10.2 | Conforms | Passed |
| Developer Removability                | 3.3.10.4 | Conforms | Passed |
| Redispersibility (Forms c,d & e only) | 3.3.10.5 | Conforms | Passed |

--- EOR ---

## Inspection Certificate

Abnahmeprüfungszeugnis DIN EN 10204.3.1

Certificat De reception

Certificado di collaudo

Keuringsrapport



**Prepared by**

A handwritten signature in black ink, appearing to read 'Zainoff'.

**Approved by**

A handwritten signature in black ink, consisting of stylized initials followed by a horizontal line.

### Notes:

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

FORMAT: MX 101.137 MC-09 Rev 28

**Magnaflux** (A Division of ITW Ltd),  
Faraday Road, South Dorcan Industrial Estate,  
Swindon, Wiltshire, SN3 5HE, UK  
Tel: +44 (0)1793 524566  
Fax: +44 (0)1793 490459  
Email: sales.eu@magnaflux.com  
www.magnaflux.eu