

**Inspection Certificate**

Abnahmeprüfungszeugnis DIN EN 10204.3.1  
 Certificat De reception  
 Certificado di collaudo  
 Keuringsrapport



<b>Batch Number</b>	<b>2411024</b>	<b>Product Name</b>	Zygly ZP-5B Water Suspendible Developer
<b>Date of Manufacture</b>	05/11/2024	<b>B.B.E.</b>	11/2029

**Specification: Specification****Specification**

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:

a) ASME Boiler and Pressure Vessel Code, 2023 Edition, Section V, Non-destructive Examination.

b) ASTM E-165/E-165M-18, Paragraph 7.1.

c) MIL-STD-2132E, March 29, 2016, Paragraph 6.1.3.

2. Meets the requirements of AMS 2644J and ASTM E 1417/E 1417M-21 Paragraph 5.1 & 6.5.1.

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

**Specification: Ion Testing Results**

Test results obtained were as follows:

Test	Section	Limit	Result
Sulphur Content			54 ppm
Halogen Content			657 ppm

**Specification: AMS 2644J Developer Results**

When sampled & tested according to paragraph 4.3.2 section 4.2.2.3 of AMS 2644J the following results were obtained:

Test	Section	Limit	Result
Developer Fluorescence	3.3.10.2		Passed
Developer Removability	3.3.10.4		Passed
Redispersibility (Forms c,d & e only)	3.3.10.5		Passed

--- EOR ---

**Prepared by**

**Approved by**

**Notes:**

- Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
- Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
- MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
- The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

**Magnaflux** (A Division of ITW Ltd),  
 Faraday Road, South Dorcan Industrial Estate,  
 Swindon, Wiltshire, SN3 5HE, UK  
 Tel: +44 (0)1793 524566  
 Fax: +44 (0)1793 490459  
 Email: sales.eu@magnaflux.com  
 www.magnaflux.eu