

Inspection Certificate

Abnahmeprüfungszeugnis DIN EN 10204.3.1

Certificat De reception

Certificado di collaudo

Keuringsrapport



Batch Number	250108	Product Name	Spotcheck SKL-SP2 Red Penetrant Aerosol
Date of Manufacture	22/01/2025 23/01/2025	B.B.E.	01/2028

Specification: Specification

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:

a) ASME Boiler and Pressure Vessel Code, 2023 Edition, Section V, Non-destructive Examination.

b) ASTM E-165/E-165M-23, Paragraph 7.1.

c) MIL-STD-2132E, March 29, 2016, Paragraph 6.1.3.

2. Meets the requirements of EN ISO 3452-1, EN ISO 3452-2 (Sensitivity level 2), AMS 2644J and ASTM E 1417/E 1417M-21 EDT1 Paragraph 5.1& 6.5.1.

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Specification

Specification: Ion Testing Results

Test results obtained were as follows:

Test	Section	Limit	Result
Sulphur Content (S)		Conforms	0.0029%
Halogen Content (F + Cl)		Conforms	0.0039%

Specification: AMS 2644J Penetrant Results

Type 2 Penetrant

When tested according to paragraph 4.3.2 of AMS 2644J the following results were obtained:

Test	Section	Limit	Result
Viscosity	3.3.4		3.81 mm ² /s
Penetrant Removal	3.3.8.6		Passed
Water Content (SMT 18)	3.3.8.7		0.01 %

Specification: EN ISO 3452-2

When tested at the time of manufacture the following results were obtained. The information is derived from our quality checks. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of the product for any particular purpose.

Test	Section	Limit	Result
Appearance	6.1	Equal to standard	Passed
Sensitivity for ISO 3452-2 (SMT 58)	6.2	Level 2	Passed
Density (SMT 50)	6.3	0.806 - 0.890 g/cm ³	0.852 g/cm ³ @ 20°C
Corrosive Properties	6.11	No Corrosion on Magnesium Alloy	Passed
Water Content for EN ISO 3452-2	6.20	<5% (Water Wash Pen Only)	0.01 %
Flashpoint (SMT 14)	6.5	93°C Min for Bulk	104.4 °C
Viscosity	6.4 in EN ISO 3452-2	3.40 – 4.14 mm ² /s @ 38°C	3.81 mm ² /s
Sulphur Content (S)	6.12 EN ISO 3452-2	<200ppm	29ppm
Halogen Content (F + Cl)	6.12 EN ISO 3452-2	<200ppm	39ppm

--- EOR ---

Inspection Certificate

Abnahmeprüfungszeugnis DIN EN 10204.3.1

Certificat De reception

Certificado di collaudo

Keuringsrapport



Prepared by

A handwritten signature in black ink, appearing to read 'Zaino'.

Approved by

A handwritten signature in black ink, consisting of stylized initials followed by a horizontal line.

Notes:

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

FORMAT: MX 101.137 MC-09 Rev 26

Magnaflux (A Division of ITW Ltd),
Faraday Road, South Dorcan Industrial Estate,
Swindon, Wiltshire, SN3 5HE, UK
Tel: +44 (0)1793 524566
Fax: +44 (0)1793 490459
Email: sales.eu@magnaflux.com
www.magnaflux.eu