

SUBJECT: Spotcheck SKL-SP2 Red Penetrant Aerosol**AEROSOL BATCH No:** 210405**MANUFACTURE DATE:** 01-07/04/2021**B.B.E.:** APR 2024Abnahmeprüfzeugnis DIN EN 10204 3.1
Certificat De reception
Certificado di collaudo
Keuringsrapport

We hereby certify that when tested at the time of manufacture, the above material:

1. Meets the requirements of and has been tested for sulfur and halogens according to:
 - a) ASME Boiler and Pressure Vessel Code, 2019 Edition, Section V, Non-destructive Examination.
 - b) Anion analysis by ASTM D129 decomposition followed by Ion Chromatography method Annex A4.
 - c) ASTM E-165/E-165M-18, Paragraph 7.1.
 - d) MIL-STD-2132D, 11 February 2003, Paragraph 7.1, 7.1.2, 7.1.3 and Appendix C, Paragraph 40.

Test results obtained were as follows:

Ion	Batch Result
Sulfur:	0.0015 wt % of residue.
Chlorine + Fluorine:	0.0014 wt % of residue.

2. Meets the requirements of EN ISO 3452-1, EN ISO 3452-2 (Sensitivity level 2), AMS 2644H and ASTM E 1417/E 1417M-16 Paragraph 5.1& 6.5.1.

When tested according to paragraph 4.3.2 of AMS 2644H the following results were obtained:

4.2.2.1	Penetrant Tests	Section	Batch Result
	Flashpoint (PMCC)	3.3.3	104.5 °C
	Viscosity	3.3.4	3.71 mm ² /s (cSt) @ 38°C
	Penetrant Removability	3.3.8.6	Conforms
	Water Content	3.3.8.7	0.02 %

3. We further certify that the material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Certification is issued under the auspices of the Quality Assurance Manager.



(Authorised Employee)

For and on behalf of MAGNAFLUX (A DIVISION OF ITW LTD)

Notes:

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container. Bulk materials have a minimum shelf life of 5 years from date of manufacture. Aerosols have a minimum shelf life of 3 years from date of manufacture.
2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

SUBJECT: Spotcheck SKL-SP2 Red Penetrant Aerosol

AEROSOL BATCH No: 210405

MANUFACTURE DATE: 01-07/04/2021

B.B.E.: APR 2024

Specification: EN ISO 3452-2

Abnahmeprüfzeugnis DIN EN 10204 3.1
Certificat De reception
Certificado di collaudo
Keuringsrapport

When tested at the time of manufacture the following results were obtained:

Einzeleigenschaft / Characteristic	Ermittlungen nach EN ISO 3452-2 Abschnitt	Anforderungen / Quality requirement	Ergebnis / Batch testing
Appearance	6.1	Equal to Std	Pass
Sensitivity	6.2	Level 2	Pass
Density	6.3	0.806 – 0.890 g/cm ³ @ 20°C	0.852 g/cm ³
Viscosity	6.4	3.24 – 3.96 mm ² /s @ 38°C	3.71 mm ² /s
Flashpoint	6.5	93°C Min for Bulk	Bulk 104.5 °C Aerosol -40°C
Corrosive Properties	6.11	No Corrosion on Magnesium Alloy	Pass
Sulphur Content	6.12	< 200 ppm	15 ppm
Halogen Content	6.12	< 200 ppm	14 ppm
Water Content	6.20	< 5% (Water Wash Pen Only)	0.02%

Vorstehende Angaben sind die Ergebnisse unserer Qualitätsprüfung. Sie entbinden den Käufer nicht von einer Eingangsprüfung und haben nicht die Bedeutung, die Eignung des Produktes für einen konkreten Einsatzzweck zu sichern.

The above information is derived from our quality checks. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of the product for any particular purpose.

Certification is issued under the auspices of the Quality Assurance Manager.



(Authorised Employee)

For and on behalf of MAGNAFLUX (A DIVISION OF ITW LTD)