### **Inspection Certificate**

Abnahmeprüfungszeugnis DIN EN 10204.3.1 Certificat De reception Certificado di collaudo Keuringsrapport



Batch Number	2507029	Product Name	Magnaglo MG-601
Date of Manufacture	16/07/2025	B.B.E.	07/2030

# **Specification: Specification**

A. ASME Boiler and Pressure Vessel Code, 2023 Edition, Section V, Non-destructive Examination.

B. ASTM E 709-21, Paragraphs 8.1.2, 8.2, 8.3, 8.5, 8.5.5, 8.5.3 & 20.6.3

C. ASTM E-1444/E144M-25, Paragraphs 5.5.2 & 5.5.4

D. MIL-STD-2132E, March 29, 2016,

E. EN ISO 9934-2

F. KTA 3905, Paragraph B 3.2.2.2 (2)

We further certify that this material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.

Test	Section	Limit	Result
Specification			Passed

#### Specification: AMS-3044H

We hereby certify that the above Fluorescent Magnetic Particle Inspection Material meets the requirements of Aerospace Material specification AMS-3044H, Magnetic Particles, Fluorescent, Wet method, Dry powder.

Test	Section	Limit	Result
Particle Size by Sieve (SMT 16)	3.2.3	Pass 45 μ mesh: 98% Min Conforms	99.54%
Sensitivity-Ketos Ring Indications (SMT 24)	3.2.5	7 Hole indications shown	7
Durability	3.2.4	Retain initial sensitivity, colour and brightness	Passed
Contamination	3.2.1	No foreign material, scum or agglomeration	Passed

## **Specification: Test Results**

Specification, rest results				
Test	Section	Limit	Result	
Colour		Brown	Passed	
Colour under UV		Fluorescence : Yellow Green	Passed	
Particle Size - da (SMT 41)		Report	6.49µm	
Particle Size - dl (SMT 41)		Report	5.97μm	
Particle Size - du (SMT 41)		Report	7.26µm	
Fluorescent Co-Efficient		Shall be within 10% of the type testing	96.19%	
Storage Stability		5 Years	Passed	

#### **Inspection Certificate**

Abnahmeprüfungszeugnis DIN EN 10204.3.1 Certificat De reception Certificado di collaudo Keuringsrapport



Prepared by

Approved by

#### Notes:

- 1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
- 2. Most specifications require test results stated in percent, but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
- 3. MIL-STD-271, MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analysed for Sulfur and Halogens. Lower residues shall be reported.
- 4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

Magnaflux (A Division of ITW Ltd), Faraday Road, South Dorcan Industrial Estate, Swindon, Wiltshire, SN3 5HE, UK Tel: +44 (0)1793 524566 Fax: +44 (0)1793 490459 Email: sales.eu@magnaflux.com www.magnaflux.eu

FORMAT: MX 101.137 MC-09 Rev 12