

SUBJECT: 622.1 Oil Based Fluorescent MPI Ink Concentrate**BATCH No:** 2011458**MANUFACTURE DATUM / DATE:** 06/11/2020**B.B.E:** NOV 2025Abnahme prüfzeugnis DIN EN 10204 3.1
Certificat De reception
Certificado di collaudo
Keuringsrapport

We hereby certify that the above Magnetic Particle Inspection Material when diluted 1:100 by volume with an oil vehicle meeting the requirements of AMS 2641D (Type 1), meets the requirements of Aerospace Material specification AMS-3045F, Magnetic Particles, Fluorescent, Wet method, Oil vehicle.

<u>TEST</u>	<u>PARAGRAPH</u>	<u>LIMIT</u>	<u>RESULT</u>
Contamination	3.3.1	No foreign material, scum or agglomeration	Conforms
Concentration	3.3.2	0.1 - 0.4 ml magnetic particles per 100 ml	Conforms
Sensitivity	3.3.3	7 Hole indications shown	Conforms
Colour	-	Fluorescence: yellow green	Conforms

We further certify that the above Magnetic Particle Inspection Material when diluted 1:100 by volume with an oil vehicle meeting the requirements of AMS 2641C (Type 1), meets the requirements of the following specifications:

- A. ASME Boiler and Pressure Vessel Code, 2019 Edition, Section V, Non-destructive Examination.
- B. ASTM E 709-15, Paragraphs 8.1.2, 8.2, 8.3, 8.5, 8.5.3 & 8.5.5
- C. ASTM E1444/E1444M-16, Paragraphs 5.5.2.
- D. AMS 3044G (Magnetic particles used in the product)
- E. KTA 3905, Paragraph B 3.2.2.2 (2)

We further certify that this material does not contain mercury as a basic element and no mercury bearing equipment was used in its manufacture.



(Authorised Employee)

Notes:

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on the bottom of the container. Bulk materials have a minimum shelf life of 5 years from date of manufacture. Aerosols have a minimum shelf life of 3 years from date of manufacture.
2. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.

SUBJECT: 622.1 Oil Based Fluorescent MPI Ink Concentrate

Abnahme prüfzeugnis DIN EN 10204 3.1

BATCH No: 2011458

Certificat De reception

Certificado di collaudo

Keuringsrapport

MANUFACTURE DATUM / DATE: 06/11/2020

B.B.E: NOV 2025

Specification: EN ISO 9934-2.

When tested at the time of manufacture the above concentrate, diluted 1:100 by volume with an oil vehicle meeting the requirements of AMS 2641C (Type 1) the following results were obtained.

Einzeleigenschaft / Characteristic	Ermittlungen nach DIN EN ISO 9934-2 Abschnitt	Anforderungen / Quality requirement	Ergebnis / Batch testing
Eignung Performance	7.1	Anzeigefähigkeit auf Vergleichskörper 1 Ermittlung der Anzeigenlängen auf Vergleichskörper2 / (072814) Indication on reference block 1) Indication length of reference block 2 (072814)	sehr gut Gesamtlänge der beiden Anzeigen: 8.0 cm very good Total length of indication: 8.0 cm
Farbe/ Colour	7.2	Hell braune Flüssigkeit Light brown liquid	Farbe identisch/ Colour identical
Korngröße/ Particle size	7.3	d_a =Report d_i =Report d_u =Report	d_a =5.83
			d_i =4.09
			d_u =7.65
Fluoreszenzkoeffizient/ Fluorescence coefficient	7.5	Shall be within 10% of the type testing	109%
Fluoreszenz der Trägerflüssigkeit/ Fluorescence of carrier liquid	7.6	Nicht heller als Quinine-Sulfat-Lösung/ Not brighter than quinine sulphate solution	Anforderung erfüllt/ Requirement fulfilled.
Flammpunkt Flashpoint	7.7	Report	Bulk 102.5°C
Viskosität Viscosity	7.9	Bei 20°C weniger als 5mPa s Less than 5mPa s at 20°C	4.27 mPa s bei 20°C 4.27 mPa s at 20°C
Mechanische Stabilität Kurzzeittest Mechanical stability Short term test	7.10	Keine Abnahme der Empfindlichkeit Nach dem test No decrease in sensitivity after test	Anforderungen erfüllt/ Requirement fulfilled
Schäumverhalten/ Foaming	7.11	Keine signifikante Schaumbildung/ No significant foaming	Anforderungen erfüllt/ Requirement fulfilled
Lagerungsbeständigkeit/ Storage stability	7.13		5 Jahre/ 5 years

Vorstehende Angaben sind die Ergebnisse unserer Qualitätsprüfung. Sie entbinden den Käufer nicht von einer Eingangsprüfung und haben nicht die Bedeutung, die Eignung des Produktes für einen konkreten Einsatzzweck zuzusichern.

The above information is derived from our quality checks. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of the product for any particular purpose.

Certification is issued under the auspices of the Quality Assurance Manager.



(Authorised Employee)

MX 101.132 622.1 MC- 56 Rev 8