

|                |                            |                |         |
|----------------|----------------------------|----------------|---------|
| Product Name   | Spotcheck Developer SKD-S2 | Batch Number   | 26H043  |
| Date           | 08/13/2026                 | Best By Date   | 08/2031 |
| Classification | Solvent Based Developer    | Purchase Order |         |

It is hereby certified that when tested at the time of manufacture, the above listed material and batch number meets the requirements of and has been tested for Sulfur and Halogens according to:

- ASME Boiler and Pressure Vessel Code, Section V, 2007-2025 Edition, Nondestructive Examination, Article 6 Paragraph T-641 and Article 24 as applicable.
- ASTM E-165/E-165M-23 Paragraph 7.1.
- NAVSEA T9074-AS-GIB-010/271 (September 11, 2014 Rev. 1) Paragraph 5.3.1 and 5.6.2
- MIL-STD-2132D, March 29, 2016, Paragraphs 7.1, 7.1.2 and 7.1.3, Appendix C, Paragraph 40.
- NAVSEA 250-1500-1, Rev. 19, Paragraphs 12.5.1.1 and 12.5.1.1.1

The following test results were obtained:

Sulfur 42.669 ppm 0.0043 wt.% CL+F 22.825 ppm 0.0023 wt%

It is further certified that this material does not contain mercury as a basic element and that no mercury bearing equipment has been used in its manufacture.

**Specification: ASTM 1417, Paragraph 5.1**

Meets requirements

**Specification: AMS 2644J**

When tested according to paragraph 4.3.2, Sampling Plan A, the following test results were obtained:

- 4.2.2.3 Developer Tools

| Test                   | Requirements | Result |
|------------------------|--------------|--------|
| Developer Fluorescence | 3.3.10.2     | NA     |
| Developer Removability | 3.3.10.4     | PASS   |
| Redispersibility       | 3.3.10.5     | PASS   |

|                |                            |                |         |
|----------------|----------------------------|----------------|---------|
| Product Name   | Spotcheck Developer SKD-S2 | Batch Number   | 26H043  |
| Date           | 08/13/2026                 | Best By Date   | 08/2031 |
| Classification | Solvent Based Developer    | Purchase Order |         |

**Specification: ISO 3452-2**

## 5.4.1 Table 2

| Individual Property                  | Section | Requirement                                                                                                    | Result |
|--------------------------------------|---------|----------------------------------------------------------------------------------------------------------------|--------|
| Appearance                           | 6.1     | White                                                                                                          | PASS   |
| Sensitivity (30µm panel)             | 6.2     | Sensitivity Level (1(<75%) or 2 (≥75%))<br>Penetrant: SKL-SP2                                                  | 2      |
| Density                              | 6.3     | .707-.825@ 20°C (68°F)                                                                                         | 0.784  |
| Residue on evaporation/solid content | 6.13    | 13.83 - 16.94 g*                                                                                               | 15.6   |
| Flashpoint                           | 6.5     | NA                                                                                                             | NA**   |
| Corrosive Properties (Mg)            | 6.11    | No evidence of staining, pitting or corrosion                                                                  | PASS   |
| Developer Performance                | 6.15    | Fine, even, non-reflective and non-fluorescent coating, shall increase visibility of the penetrant indications | PASS   |
| Re-dispensability                    | 6.16    | Readily dispersed when stirred or agitated. Aerosol shall be suspended after 30sec shaking                     | PASS   |

\*Residue on evaporation/solid content is done from the bulk material and not the aerosol cans. Value obtained is more accurate on bulk material.

\*\*Flashpoint not required per ISO3452-2:2013 6.5.1 flashpoint measurement only required for material with nominal flash of 20°C and 110°C. Flashpoint is below 20°C

\*\*\*Testing in accordance with 5.4.3 Table 4 as applicable

Approved by:



Quality Control Manager

Notes:

1. Our batch number appears on the label of bulk containers. Aerosols have batch numbers printed on bottom of the container.
2. Most specifications require test results to be stated in percent but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
3. MIL-STD-2132 and ASME Sec V, all require that materials be subject to a procedure to evaporate off volatile solvents before analysis for Sulfur and Halogens. According to these specifications, only those residues higher than 0.005 g/100ml shall be analyzed for Sulfur and Halogens. Lower residues shall be reported.
4. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material.